

VANDENS SIURBLIAI, UAB
Įmonės kodas 144708571
PVM kodas LT447085716
Girulių g. 24, Šiauliai
LT78138, Lietuva




KASETĖ POST WASHED CARBON T/33 - 11.87 €

Gamintojas




APRAŠYMAS:

Specifikacijos • Pagaminta iš aktyvuotos anglies, naudojama geriamo vandens sistemose • Šalina iš vandens blogą kvapą, chlorą, pesticidus, pagerina vandens skonį • Maks. temperatūra 37 C • Efektyvus pralaidumas 4 litrai per min.



ACID-WASH CARBON CL-10RO T/33



◀ FLOW TASTE & ODOR REDUCTION

MAXIMUM FLOW	0.75	GPM
MAXIMUM PRESSURE	125	PSI
MAXIMUM TEMPERATURE	100	°F
SERVICE LIFE	1800	GAL

NOTE: DO NOT USE WHERE THE WATER IS MICROBIOLOGICALLY UNSAFE OR OF UNKNOWN QUALITY WITHOUT ADEQUATE DISINFECTION BEFORE OR AFTER THE UNIT. INSTALL IN COLD WATER APPLICATIONS ONLY.

INSTALLATION:

1. SHUT OFF WATER SUPPLY.
2. NOTE THE FLOW DIRECTION ON THE FILTER.
3. FOR QUICK CONNECT FITTINGS, PUSH THE TIGHTENING PIN THROUGH FREE TUBE END INTO THE HOUSING AND LOCK THE HOUSING CAP ON THE OTHER SIDE. FOR THREADED, INSTALL TEFON TAPED FITTINGS AND TIGHTEN FINALLY.
4. TURN ON THE WATER AND CHECK FOR LEAKS. IF LEAKS PERSIST, DISCONTINUE INSTALLATION.
5. PLEASE FOLLOW THE INSTRUCTIONS ON THE FILTER HOUSING.



Kimes Sals, Taiwan

KASÉTÉ POST WASHED CARBON T/33

Kodas: P.18 No.16

Kaina: . . . EUR