

VANDENS SIURBLIAI, UAB
Įmonės kodas 144708571
PVM kodas LT447085716
Girulių g. 24, Šiauliai
LT78138, Lietuva



SLĖGIO DAVIKLIS 4~20mA, Max 10bar - 92 €

Gamintojas



APRAŠYMAS:

BDF-CTA slėgio daviklių serija pasižymi aukšta kokybe, dideliu stabilumu, mažu dydžiu, svoriu, kompaktiška struktūra. $\pm 0,5$, $\pm 1,0\%$ F.S tikslumas Aukštas stabilumas, didelis patikimumas Skaitmeninis kalibravimas Taikymas: kompresoriai, vandens tiekimas, hidraulinis valdymas, oro kondicionierius, vandens slėgio stotis ir t.t... [TECHNINIŲ SPECIFIKACIJŲ DUOMENYS](#)

Parameter	Value		
Measurement range	0~6bar,0~10bar,0~16bar,0~25bar,0~40bar		
Overload pressure	1.5 * pressure range		
Broken pressure	3 * pressure range		
Accuracy	±1.0%F.S		
Stability	Typical 0.5% F.S, maximum: 1.0 %F.S		
Operating temperature	-40C~100C		
Compensation temperature	-10C~80C		
Medium compatibility	Corrosive medium compatible with 1Cr18Ni9Ti,Ceramic		
Wires	Two-wire	Three-wire	
Output signal	4~20mA	0.5-4.5V	
Supply voltage	10~30Vdc	5Vdc	10~30V dc
Load resistance	(U-10)/0.02(Ω)	≥100KΩ	
Insulation	≥100MΩ@50V		
Electrical connection	DIN43650, Packard,M12 Seial, Cable		
Shell/Wire protection	IP67		
Pressure form	Gauge G, Absolute A		
Pressure port	G1/2 G1/4 NPT1/4 M20×1.5 7/16-20UNF		
Response time	10ms		
Certification	CE,Intrinsic-safety explosion E, Isolated explosion-proof D		
EMC	EMI:EN50081-1/-2, EMS:EN50082-2		

