



Designed to provide easy access for grey water pumping applications such as kitchens and utility rooms, convenient covers allow simple service and maintenance of the pump without having to remove it.



SANIACCESS® PUMP



PUMP TECHNICAL DATA

Maximum flow rate	80 L/min
Shut-off head (Q=0 l/min)	8 m
Vertical and horizontal discharge	5 m / 50 m
IP rating	IP 44
Tank volume	11,7 L
Free passage	8 mm
Discharge pipe diameter	Ø ext. 32 mm
Inlets diameter	3 inlets Ø ext. 40 mm
Low inlets height (compared to ground level)	44 mm
Activation level ON (compared to ground level)	95 mm
Activation method	Membrane
Maximum admissible waste water temperature	75°C (max 5 min)
Weight	7,2 kg
Non-return valve included	

MOTOR DATA

Electrical power supply	
Single-phase	220-240 V / 50-60 Hz
Electrical power rating	400 W
Maximum current input	1,7 A
Electrical class	I
Thermally protected	
Oil-filled	

MATERIALS

Motor body	Polyamide
Pump cover plate	Polyamide
Impeller	Polypropylene
Motor shaft	Stainless steel
O-Ring	Nitrile
Sealing ring	Nitrile

Double access:

- ➔ To the basket area for easy removal of any large objects that may have been accidentally flushed
- ➔ To the electrical components for periodic maintenance

