



Diesel fire pump with a capacity of 10 m<sup>3</sup>/h flow and 60 mwc, self-priming, single-stage, horizontal-type, centrifugal pump directly coupled with diesel engine, electrical starter, 5m suction hose, 20m fabric fire hose, fairlead inlet and outlet fast connection, water spray lance, wheeled mobile fire pump. Ability to deliver both water and foam if optional foam delivery mixer and foam lance are added. There is a redresser to charge battery which is inside of control panel. When the mobile diesel fire fighting set does not work, the battery is charged by the redresser with 220V voltage.

## DIESEL PUMP SPECIFICATIONS

<b>Body</b>	Cast Iron
<b>Fan</b>	Aluminum
<b>Seal</b>	Mechanical
<b>Inlet - Outlet Diameter</b>	2"
<b>Pump Capacity</b>	10 m <sup>3</sup> /h - 6 Bar

## DIESEL MOTOR SPECIFICATIONS

10 HP, 3600 rpm, air cooled engine
4 cycle, single cylinder, diesel engine
Manual operation
Electrical start/stop
12Vdc battery
Voltaj : 220-230V - 50Hz
Oil pressure safety
Fuel Tank: 5 L
Fuel Consumption: 1,8 lt/h

## DIMENSIONS

