

Data: 07/07/2021

**60000332000: NM 25/160A/A**

## PUMP AND MOTOR DATA

<b>n (rpm):</b>	2900	<b>Motor phase:</b>	3~
<b>N. of impellers:</b>	1	<b>Un (V):</b>	230/400
<b>Max working pressure (bar):</b>	10	<b>fn (Hz):</b>	50
<b>H max (m):</b>	36.50	<b>Poles:</b>	2
<b>H min (m):</b>	26.00	<b>In (A):</b>	7.5 / 4.3
<b>Q min (mc/h):</b>	3.00	<b>PF:</b>	0.81
<b>Q max (mc/h):</b>	12.00	<b>Insulation class:</b>	F
<b>Pn (kW):</b>	1.50	<b>Duty:</b>	S1
<b>Pn (HP):</b>	2.00	<b>Min liquid temperature (°C):</b>	-10.00 °C
<b>Impeller diameter (mm):</b>	161.50	<b>IE:</b>	IE3-84.2
<b>Motor type:</b>	IM	<b>Weight (kg):</b>	22.572

## MATERIALS

<b>Pump Casing:</b>	Cast iron GJL 200 EN 1561	<b>Shaft:</b>	Cr-Ni steel 1.4305 EN 10088 (AISI 303)
<b>Lantern Bracket:</b>	Cast iron GJL 200 EN 1561	<b>Mechanical Seal:</b>	Carbon-Ceramic-NBR
<b>Impeller:</b>	Brass P-Cu Zn 40 Pb 2 UNI 5705		

Data: 07/07/2021

60000332000: NM 25/160A/A

