

Data: 22/05/2020

60400303000: NM 32/20A/B

PUMP AND MOTOR DATA


n (rpm):	2900	Motor phase:	3~
Max working pressure (bar):	10	Un (V):	400/690
H max (m):	57.50	fn (Hz):	50
H min (m):	49.00	Poles:	2
Q min (mc/h):	6.60	In (A):	9.6 / 5.5
Q max (mc/h):	16.80	PF:	0.85
Pn (kW):	4.00	Min liquid temperature (°C):	-10.00 °C
Pn (HP):	5.50	Weight (kg):	52.500
Impeller diameter (mm):	204.00		

MATERIALS

Pump Casing:	Cast iron GJL 200 EN 1561	Shaft:	Chrome steel 1.4104 EN 10088 (AISI 430F)
Lantern Bracket:	Cast iron GJL 200 EN 1561	Mechanical Seal:	Carbon-Ceramic-NBR
Impeller:	Brass P-Cu Zn 40 Pb 2 UNI 5705	Counter Flanges:	Steel S235JR 1.0038 EN 10025-2

Data: 22/05/2020

60400303000: NM 32/20A/B



Data: 22/05/2020

60400303000: NM 32/20A/B

DIMENSIONS (MM)

dn1: 50
dn2: 32
a: 80.00 mm
m1: 100.00 mm
m2: 70.00 mm
n1: 240.00 mm
n2: 190.00 mm
n3: 60.00 mm
b: 50.00 mm
l1: 140.00 mm
l2: 140.00 mm
g1: 12.00 mm
h1: 160.00 mm
h2: 180.00 mm
w: 295.00 mm
fM: 475.00 mm

