

# JetFlex® CBD 105 Coarse Bubble Diffuser





## Membrane material

Silicone

## Diffuser body

Reinforced Polypropylene (PP-GF) with R 3/4" external tapered thread



## Dimensions

Overall Diameter	Total Height	Threaded Length	Membrane Thickness
105 mm	45 mm	25 mm	2 mm



## Installation

You may install CBD 105 using our rubber saddle (EPDM) or our plastic saddle clamp. Please see our brochure "Accessories" for details and further alternatives.

## Performance data

Airflow	Headloss	SSOTE
Minimum: 2 m <sup>3</sup> /h (33 liters/minute) @ STP	10 hPa	2 %/m
Maximum: 25 m <sup>3</sup> /h (420 liters/minute) @ STP	40 hPa	1 %/m

Coarse bubble diffusers are mainly used through mixing capabilities. The rising air induces a strong current, thus removing sludge from the bottom of the tank. They are therefore a very good alternative for many mechanical aeration systems.



**Jäger Umwelt-Technik GmbH**  
 Ruscheplattenstraße 14  
 31137 Hildesheim  
 Germany  
 ☎ +49 5121 9138 900  
 📠 +49 5121 9138 999  
 www.jaeger-envirotech.com  
 info@jaeger-envirotech.com



### Disclaimer

We exclude any liability for the information and product presentations provided. Contents of technical character are based on the date of publication. Existing copyrights and rights to the use of names remain unaffected.

