


Technical Data Sheet FLOAT SWITCH, Heavy Duty

The product described below is manufactured in according to ISO 9001:2000 Quality System Standards and conforms to the following technical specifications

	<p style="text-align: center;">AS3</p> <p style="text-align: center;">for automatic on/off bilge pump control prevents rapid on/off cycling</p> <p style="text-align: center;">Mercury Free</p>
<p>PART NUMBER</p>	<p>16100310</p>
<p>VOLT</p>	<p>12 / 24 VDC</p>
<p>AWG / CABLE LENGTH</p>	<p>2 x AWG 16 / 900 mm</p>
<p>CONTACTS</p>	<p>d. 5.5 mm Copper Contacts</p>
<p>OPERATING CURRENT</p>	<p>20 A Maximum (at 12 VDC) – 10 A Maximum (at 24 VDC)</p>
<p>OPERATING DUTY CYCLE (recommended)</p>	<p>INTERMITTENT</p>
<p>TEMPERATURE RANGE</p>	<p>-25 °C / +60 °C</p>
<p>WATER LEVEL ON / OFF</p>	<p>51 mm / 19 mm</p>
<p>PROTECTION Standards</p>	<p>EN 60529 - IP 67 ISO 8846</p>
<p>E.M.C Standards</p>	<p>EN 61000-6-1 EN 61000-6-3</p>
<p>ELECTRICAL Standard</p>	<p>ISO 10133</p>
<p>DIMENSIONS Length x Width x Height</p>	<p>127 x 42 x 110 mm</p>
<p>NET WEIGHT</p>	<p>0,1 kg</p>