

TY 6

60 Hz - 2 POLES

TECHNICAL DATA

Inlet connections	1" 1/2 F BSPP
Outlet connections	1" M BSPP
Max. flow rate*	6,4 m3/h
Max. delivery head*	6,5 m
BEP flow rate*	4,3 m3/h
BEP delivery head*	4 m
Max. viscosity	100 cps
Impeller	Semi-opened Ø 79
Weight (no motor)	kg
Min. temperature	-5°C
Max. temperature	+65°C



EAC

CE

UK
CA

POLYPROPYLENE

COMPOSITION

MODEL	CASING	O-RING	LENGTHS AVAILABLE	CONNECTIONS	FRAME SIZE	MOTOR VERSION
TY006	P = PP	D = EPDM V = VITON	250 500 800 1000	1 = BSPP STD 2 = FLANGED	71 80 90	IE = IEC FLANGE - = NO MOTOR

MOTOR SPECIFICATION

N° POLES	2	PROTECTION	IP 55
RPM	3500	FLANGES	IEC
FREQUENCY	60 Hz	DESIGN	B5



FLUIMAC S.r.l. - Via Brescia, 1 - 21049 - Tradate - VA - ITALY
info@fluimac.com - www.fluimac.com
tel. +39 0331 866688 - Fax +39 0331 864870
P.I./VAT 03259160129






TY 6

60 Hz - 2 POLES

PERFORMANCES

The curves and performance values refer to pumps with free delivery outlet with water at 20 °C, and **60 Hz** and **2 poles motor**.

* These data may vary according to the construction materials, hydraulic conditions and the length of the pump.



FLUIMAC S.r.l. - Via Brescia, 1 - 21049 - Tradate - VA - ITALY
info@fluimac.com - www.fluimac.com
tel. +39 0331 866688 - Fax +39 0331 864870
P.I./VAT 03259160129






TY 6

60 Hz - 2 POLES

DIMENSION [mm]

Technical data are approximate and not binding for the manufacturer who reserves the right to change them without notice at any time



L
Length
available
[mm]

250
500
800
1000

DIMENSIONS

*depends on the manufacturer

FRAME	KW	Weight [kg]*	A' [mm]	B' [mm]	C' [mm]	LT [mm]
IEC 71	0,37	5,6	225	112	160	147
IEC 71	0,55	6,1	225	112	160	147
IEC 80	0,75	9,1	250	132	200	147



FLUIMAC S.r.l. - Via Brescia, 1 - 21049 - Tradate - VA - ITALY
info@fluimac.com - www.fluimac.com
 tel. +39 0331 866688 - Fax +39 0331 864870
 P.I./VAT 03259160129

