

IMM 50A



Descrizione

They are suitable for the transfer of liquids containing impurities up to 3 mm in size. The hydraulic components: impeller, scroll and pump body in PBT, allow it to be used with water, emulsions and oily substances in general, with a viscosity not exceeding 21 cSt (3 ° Engel). The liquid temperature must not exceed 70 ° C.

Applicazioni

They are commonly used on:

- machine tools (milling machines-lathes-drills)
- glass processing machines (TRI version)
- air conditioning and conditioning systems

They should normally be installed on a tank with a capacity proportionate to the flow rate, about 2-3 cm from the bottom. It is important to check that the maximum liquid level in the tank always remains 3-4 cm lower than the support flange (see figure).

In cases where the liquid is particularly dirty it is advisable to build the tank with

compartments, to allow the deposit of sludge before it is fished out by the pump. For different uses it is advisable to consult our Technical Department.

Dati di targa

Attributo	Valore
Potenza 1 (kW)	0,09
Potenza 2 (kW)	0,04
Conn. Idraulica (")	3/8
Portata Massima (l/min)	22
Prevalenza Massima (mt)	2,5
Dim max impurità (mm)	3
Tipo girante	Open

Materiali

	Materiale	Opzione Materiale
Girante	Nylon	
Corpo Pompa	PBT	
Chiocciola	PBT	
Albero	Steel	Aisi 316