

FFGROUP[®]

QUALITY POWER TOOLS

PETROL WATER PUMPS



WATER PUMPING (PETROL)
PETROL WATER PUMPS

SEMI-PRO USE



PUMP PERFORMANCE				
m³/h	13,2	11,5	9,1	4,6
Height (m)	4,5	7,4	10,6	14,2

- Surface pump, suitable for transporting clean water without particles
- Pump body and impeller made of aluminum
- Extremely light, with ergonomic design for easy transport
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine

H205 x L80 x W120cm - 30pcs

GWP 40/79 PLUS
PETROL WATER PUMP

ARTICLE NUMBER	46632
Tech Specs	
Type	Clean water
Suction port diameter	1,5"
Discharge port diameter	1,5"
Total head lift	16 m
Max flow	14 m³/hr
Max. suction head lift	7 m
Pump body material	Aluminum
Impeller material	Aluminum
Cylinder displacement	78,5 cc
Rated power input	2,6 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	1,8 L
Starting mode	Recoil
Weight	14,0 kg
Includes	
Filter	✓
Box	1 pc

SEMI-PRO USE



PUMP PERFORMANCE			
m³/h	28,4	22,0	8,0
Height (m)	6,1	14,1	19,0

- Surface pump, suitable for transporting clean water without particles
- Aluminum pump body and cast iron impeller
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine

H183 x L80 x W120cm - 16pcs

GWP 50/209 PLUS
PETROL WATER PUMP

ARTICLE NUMBER	46633
Tech Specs	
Type	Clean water
Suction port diameter	2,0"
Discharge port diameter	2,0"
Total head lift	28 m
Max flow	36 m³/hr
Max. suction head lift	8 m
Pump body material	Aluminum
Impeller material	Cast iron
Cylinder displacement	209 cc
Rated power input	7,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	3,6 L
Starting mode	Recoil
Weight	21,0 kg
Includes	
Filter	✓
Box	1 pc

PRO USE



PUMP PERFORMANCE				
m³/h	28,4	22,0	18,1	8,0
Height (m)	6,1	14,1	19,0	16,6

- Surface pump, suitable for transporting clean water without particles
- Aluminum pump body and cast iron impeller
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty

H183 x L80 x W120cm - 16pcs

GWP 50/212 PRO
PETROL WATER PUMP

ARTICLE NUMBER	46634
Tech Specs	
Type	Clean water
Suction port diameter	2,0"
Discharge port diameter	2,0"
Total head lift	28 m
Max flow	36 m³/hr
Max. suction head lift	8 m
Pump body material	Aluminum
Impeller material	Cast iron
Cylinder displacement	212 cc
Rated power input	7,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	3,6 L
Starting mode	Recoil
Weight	23,5 kg
Includes	
Filter	✓
Box	1 pc

PRO USE



PUMP PERFORMANCE				
m³/h	55,0	40,5	34,1	16,5
Height (m)	8,9	19,6	21,5	16,0

- Surface pump, suitable for transporting clean water without particles
- Aluminum pump body and cast iron impeller
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty


H197 x L80 x W120cm - 16pcs

GWP 80/212 PRO
PETROL WATER PUMP

ARTICLE NUMBER	46635
Tech Specs	
Type	Clean water
Suction port diameter	3,0"
Discharge port diameter	3,0"
Total head lift	28 m
Max flow	60 m³/hr
Max. suction head lift	8 m
Pump body material	Aluminum
Impeller material	Cast iron
Cylinder displacement	212 cc
Rated power input	7,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	3,6 L
Starting mode	Recoil
Weight	25,5 kg
Includes	
Filter	✓
Box	1 pc

WATER PUMPING (PETROL)
PETROL WATER PUMPS

PRO USE



PUMP PERFORMANCE				
m³/h	55,2	48,1	26,6	13,8
Height (m)	6,7	11,5	19,4	23,0


- Surface pump, suitable for transporting dirty water with soft particles
- Aluminum pump body and cast iron cutter impeller
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty

H203 x L80 x W120cm - 8pcs

GWP 80/212 ST PRO
PETROL WATER PUMP

ARTICLE NUMBER	46636
Tech Specs	
Type	Semi-Trash
Suction port diameter	3,0"
Discharge port diameter	3,0"
Total head lift	26 m
Max flow	60 m³/hr
Max. suction head lift	8 m
Max grain size	25,4 mm
Pump body material	Aluminum
Impeller material	Cast iron
Cylinder displacement	212 cc
Rated power input	7,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	3,6 L
Starting mode	Recoil
Weight	36,0 kg
Includes	
Filter	✓
Box	1 pc

PRO USE



PUMP PERFORMANCE				
m³/h	54,7	46,1	32,7	11,2
Height (m)	11,1	15,6	19,5	23,7

- Surface pump, suitable for transporting dirty water with hard particles
- Aluminum pump body and cast iron cutter impeller
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty

H192 x L80 x W120cm - 6pcs

GWP 80/301 FT PRO
PETROL WATER PUMP

ARTICLE NUMBER	46637
Tech Specs	
Type	Trash
Suction port diameter	3,0"
Discharge port diameter	3,0"
Total head lift	26 m
Max flow	66 m³/hr
Max. suction head lift	8 m
Max grain size	25,4 mm
Pump body material	Aluminum
Impeller material	Cast iron
Cylinder displacement	301 cc
Rated power input	10,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	5,4 L
Starting mode	Recoil
Weight	61,0 kg
Includes	
Filter	✓
Box	1 pc

PRO USE



PUMP PERFORMANCE				
m ³ /h	23,9	21,6	18,9	13,2
Height (m)	26,9	31,9	36,8	46,2

- High pressure surface pump, suitable for transport with pressure of clean water without particles
- Pump body and impeller made of aluminum
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty

H199 x L80 x W120cm - 16pcs

GWP 50/212 H PRO
PETROL WATER PUMP

ARTICLE NUMBER	46638
Tech Specs	
Type	High lift
Suction port diameter	2,0"
Discharge port diameter	2,0"
Total head lift	50 m
Max flow	30 m ³ /hr
Max. suction head lift	7 m
Pump body material	Aluminum
Impeller material	Aluminum
Cylinder displacement	212 cc
Rated power input	7,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	3,6 L
Starting mode	Recoil
Weight	26,0 kg
Includes	
Filter	✓
Box	1 pc

PRO USE



PUMP PERFORMANCE				
m ³ /h	14,9	12,8	8,6	4,9
Height (m)	44,6	51,1	57,0	69,7

- High pressure surface pump, suitable for transport with pressure of clean water without particles
- Pump body, two-stage aluminum impeller and 3 outlets
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty

H197 x L80 x W120cm - 16pcs

GWP 50/212 H2 PRO
PETROL WATER PUMP

ARTICLE NUMBER	46639
Tech Specs	
Type	High lift
Suction port diameter	2,0"
Discharge port diameter	2,0", 1,5", 1,5"
Total head lift	80 m
Max flow	16 m ³ /hr
Max. suction head lift	7 m
Pump body material	Aluminum
Impeller material	Aluminum
Cylinder displacement	212 cc
Rated power input	7,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	3,6 L
Starting mode	Recoil
Weight	26,0 kg
Includes	
Filter	✓
Box	1 pc

WATER PUMPING (PETROL)
PETROL WATER PUMP

PRO USE



PUMP PERFORMANCE				
m ³ /h	26,8	24,2	17,8	8,5
Height (m)	31,1	41,3	59,9	78,7

- High pressure surface pump, suitable for transport with pressure of clean water without particles
- Cast iron pump body and aluminum impeller
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty

H179 x L80 x W120cm - 6pcs

GWP 50/389 H PRO
PETROL WATER PUMP

ARTICLE NUMBER	46640
Tech Specs	
Type	High lift
Suction port diameter	2,0"
Discharge port diameter	2,0"
Total head lift	90 m
Max flow	30 m ³ /hr
Max. suction head lift	7 m
Pump body material	Cast iron
Impeller material	Aluminum
Cylinder displacement	389 cc
Rated power input	13,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	6,5 L
Starting mode	Recoil
Weight	60,0 kg
Includes	
Filter	✓
Box	1 pc

PRO USE

4-STROKE
212cc

35m
MAX HEIGHT

32,0 m³/h
MAX FLOW

2"
SUCTION DIAMETER

2"
DISCHARGE DIAMETER

23
Kg

— FOR —
CHEMICALS

EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628



PUMP PERFORMANCE				
m ³ /h	31,9	28,7	24,2	18,4
Height (m)	10,0	17,2	21,8	25,3

- Surface pump, suitable for transporting chemicals (PH 4 - 11), biodiesel or seawater, without particles
- Pump body and impeller made of polymer material for resistance to oxidation
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty

H197 x L80 x W120cm - 16pcs

GWP 50/212 CH PRO
PETROL WATER PUMP

ARTICLE NUMBER	46641
Tech Specs	
Type	Chemical
Suction port diameter	2,0"
Discharge port diameter	2,0"
Total head lift	35 m
Max flow	32 m ³ /hr
Max. suction head lift	7 m
Pump body material	Polymer
Impeller material	Polymer
Cylinder displacement	212 cc
Rated power input	7,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	3,6 L
Starting mode	Recoil
Weight	23,0 kg
Includes	
Filter	✓
Box	1 pc

PRO USE

4-STROKE
212cc

26m
MAX HEIGHT

60,0 m³/h
MAX FLOW

3"
SUCTION DIAMETER

3"
DISCHARGE DIAMETER

25
Kg

— FOR —
CHEMICALS

EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628



PUMP PERFORMANCE				
m ³ /h	56,1	44,8	31,1	19,0
Height (m)	5,0	12,5	20,1	24,7

- Surface pump, suitable for transporting chemicals (PH 4 - 11), biodiesel or seawater, without particles
- Pump body and impeller made of polymer material for resistance to oxidation
- Robust steel frame, heavy duty
- Low oil level safety
- Two-stage air filter
- Anti-vibration system
- Air-cooled 4-stroke engine, heavy duty

H207 x L80 x W120cm - 16pcs

GWP 80/212 CH PRO
PETROL WATER PUMP

ARTICLE NUMBER	46642
Tech Specs	
Type	Chemical
Suction port diameter	3,0"
Discharge port diameter	3,0"
Total head lift	26 m
Max flow	60 m ³ /hr
Max. suction head lift	7 m
Pump body material	Polymer
Impeller material	Polymer
Cylinder displacement	212 cc
Rated power input	7,0 hp
Rated speed	3.600 min ⁻¹
Fuel tank capacity	3,6 L
Starting mode	Recoil
Weight	25,0 kg
Includes	
Filter	✓
Box	1 pc

FFGROUP[®]

QUALITY POWER TOOLS

PETROL **GENERATORS**



PRO USE

60cc
1100 VA POWER

FUEL
MAX 2,60 Lt

OVERLOAD PROTECTION

EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628

12V
IDEAL FOR OLIVE HARVESTERS

LOW NOISE

14 Kg

INVERTER
TECHNOLOGY

NEW



- Strong DC output, ideal for powering 12 V equipment like olive harvesters
- Powerful air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- Inverter voltage stabilization technology, for safe power supply of sensitive electronic devices
- Electronic stability control (ESC) for fuel economy
- Low oil level safety
- Low noise operation
- Extremely light, with ergonomic design for easy transport
- Overload protection

H000 x L00 x W000cm - 00pcs

GPG 1100i PRO
PETROL INVERTER GENERATOR

ARTICLE NUMBER	47524
Tech Specs	
Rated voltage	230 V 50 Hz
Max power	1,1 kVA
Rated power input	1,0 kVA
Rated output current	4,4 A
Voltage regulator	INVERTER
Outlet (AC)	1x 16 A
Outlet (DC)	1x 60 A
Cylinder displacement	60,0 cc
Fuel tank capacity	2,6 L
Running time	5,5 h
Starting mode	Recoil
Engine speed control	ESC
Size (L x W x H)	430x240x370 mm
Weight	14,0 kg
Box	1 pc

PRO USE

79,7cc
2000 WATT POWER

FUEL
MAX 4,00 Lt

OVERLOAD PROTECTION

EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628

22 Kg

LOW NOISE




- Powerful air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- Inverter voltage stabilization technology, for safe power supply of sensitive electronic devices
- Electronic stability control (ESC) for fuel economy
- Parallel connection outlets for double output power
- 12V and USB charging outlet
- Low oil level safety
- Low noise operation
- Extremely light, with ergonomic design for easy transport
- Overload protection

H211 x L80 x W120cm - 24pcs

GPG 2000i PRO
PETROL INVERTER GENERATOR

ARTICLE NUMBER	46100
Tech Specs	
Maximum output power	2.000 W
Rated output power	1.800 W
Rated Current (AC)	7,8 A
Voltage regulator	Inverter
Outlet (AC)	1 x 16 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	79,7 cc
Fuel tank capacity	4 L
Running time	4,0 h
Size (L x W x H)	498x290x459 mm
Weight	22,0 kg
Includes	
Wheel	✗
Engine smart control (ESC)	✓
Recoil / Electric starting mode	✓ / ✗
Parallel operation kit outlets	✓
Battery cable (DC)	✓
Box	1 pc



Parallel connection kit not included

PARALLEL CONNECTION KIT FOR INVERTER GENERATORS, 32A
ARTICLE NUMBER: 46557

PRO USE

 **2500**
WATT
POWER


EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628

 **FUEL**
MAX **4,50** Lt
OVERLOAD
PROTECTION

 **24**
LOW NOISE



- Powerful air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- Inverter voltage stabilization technology, for safe power supply of sensitive electronic devices
- Electronic stability control (ESC) for fuel economy
- Parallel connection outlets for double output power
- 12V and USB charging outlet
- Low oil level safety
- Low noise operation
- Extremely light, with ergonomic design for easy transport
- Overload protection



Parallel connection kit not included

PARALLEL CONNECTION KIT FOR INVERTER GENERATORS, 32A
ARTICLE NUMBER: 46557

H207 x L80 x W120cm - 20pcs

GPG 2500i PRO
PETROL INVERTER GENERATOR

ARTICLE NUMBER	46101
Tech Specs	
Maximum output power	2.500 W
Rated output power	2.300 W
Rated Current (AC)	10,0 A
Voltage regulator	Inverter
Outlet (AC)	1 x 16 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	120,0 cc
Fuel tank capacity	4,5 L
Running time	3,0 h
Size (L x W x H)	520x320x460 mm
Weight	24,0 kg
Includes	
Wheel	✘
Engine smart control (ESC)	✓
Recoil / Electric starting mode	✓ / ✘
Parallel operation kit outlets	✓
Battery cable (DC)	✓
Box	1 pc

PRO USE

 **3500**
WATT
POWER

EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628

 **FUEL**
MAX **8,30** Lt
OVERLOAD
PROTECTION


 **44**
LOW NOISE



INVERTER
TECHNOLOGY



- Powerful air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- Inverter voltage stabilization technology, for safe power supply of sensitive electronic devices
- Electronic stability control (ESC) for fuel economy
- Parallel connection outlets for double output power
- 12V and USB charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Low noise operation
- Electric start and battery
- Large fuel tank for additional running time
- Ergonomic design and wheels for easy transport
- Overload protection



Parallel connection kit not included

PARALLEL CONNECTION KIT FOR INVERTER GENERATORS, 32A
ARTICLE NUMBER: 46557

H177 x L80 x W120cm - 6pcs

GPG 3500iE PRO
PETROL INVERTER GENERATOR

ARTICLE NUMBER	46102
Tech Specs	
Maximum output power	3.500 W
Rated output power	3.200 W
Rated Current (AC)	13,9 A
Voltage regulator	Inverter
Outlet (AC)	2 x 16 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	212,0 cc
Fuel tank capacity	8,3 L
Running time	5,0 h
Size (L x W x H)	590x456x511 mm
Weight	44,0 kg
Includes	
Wheel	x2
Engine smart control (ESC)	✓
Recoil / Electric starting mode	✓ / ✓
Parallel operation kit outlets	✓
Battery cable (DC)	✓
Box	1 pc

SEMI-PRO USE



3000 WATT POWER



OVERLOAD PROTECTION



- Powerful air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Large fuel tank for additional running time
- Extremely light, with ergonomic design for easy transport
- Overload protection

H203 x L80 x W120cm - 16pcs

GPG 3000 PLUS
PETROL GENERATOR

ARTICLE NUMBER	46093
Tech Specs	
Maximum output power	3.000 W
Rated output power	2.700 W
Rated Current (AC)	11,7 A
Voltage regulator	AVR
Outlet (AC)	2 x 16 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	212,0 cc
Fuel tank capacity	15,0 L
Fuel Consumption	2,0 L/h
Size (L x W x H)	593×465×458 mm
Weight	41,0 kg
Includes	
Wheel	✘
Recoil / Electric starting mode	✓ / ✘
Box	1 pc

HEAVY DUTY



3000 WATT POWER



OVERLOAD PROTECTION



- Powerful and heavy duty air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- LED work light
- Extra large fuel tank for maximum running time
- Extremely light, with ergonomic design for easy transport
- Overload protection
- 2 year warranty, even for professional use

H219 x L80 x W120cm - 12pcs

GPG 3000 HD
PETROL GENERATOR

ARTICLE NUMBER	46096
Tech Specs	
Maximum output power	3.000 W
Rated output power	2.700 W
Rated Current (AC)	11,7 A
Voltage regulator	AVR
Outlet (AC)	2 x 16 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	212,0 cc
Fuel tank capacity	18,0 L
Fuel Consumption	2,0 L/h
Size (L x W x H)	600×465×493 mm
Weight	46,0 kg
Includes	
Wheel	✘
Recoil / Electric starting mode	✓ / ✘
Box	1 pc


SEMI-PRO USE



6000
WATT
POWER



- Powerful air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Large fuel tank for additional running time
- Overload protection



**HANDLE AND WHEELS
TRANSPORT KIT**
ARTICLE NUMBER: 46682

H186 x L80 x W120cm - 6pcs

**GPG 6000 PLUS
PETROL GENERATOR**

ARTICLE NUMBER	46094
Tech Specs	
Maximum output power	6.000 W
Rated output power	5.500 W
Rated Current (AC)	23,9 A
Voltage regulator	AVR
Outlet (AC)	1 x 16 A, 1 x 32 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	420,0 cc
Fuel tank capacity	25,0 L
Fuel Consumption	3,0 L/h
Size (L x W x H)	683x540x542 mm
Weight	73,0 kg
Includes	
Wheel	✘
Recoil / Electric starting mode	✓ / ✘
Box	1 pc


SEMI-PRO USE



6000
WATT
POWER



- Powerful air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Electric start and battery
- Large fuel tank for additional running time
- Overload protection




**HANDLE AND WHEELS
TRANSPORT KIT**
ARTICLE NUMBER: 46682

H186 x L80 x W120cm - 6pcs

**GPG 6000E PLUS
PETROL GENERATOR**

ARTICLE NUMBER	46095
Tech Specs	
Maximum output power	6.000 W
Rated output power	5.500 W
Rated Current (AC)	23,9 A
Voltage regulator	AVR
Outlet (AC)	1 x 16 A, 1 x 32 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	420,0 cc
Fuel tank capacity	25,0 L
Fuel Consumption	3,0 L/h
Size (L x W x H)	683x540x542 mm
Weight	78,0 kg
Includes	
Wheel	✘
Recoil / Electric starting mode	✓ / ✓
Box	1 pc

HEAVY DUTY




- Powerful and heavy duty air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Electric start and battery
- LED work light
- Extra large fuel tank for maximum running time
- Wheels for easy transport
- Overload protection
- 2 year warranty, even for professional use

H195 x L80 x W120cm - 6pcs

GPG 6000E HD
PETROL GENERATOR

ARTICLE NUMBER	46097
Tech Specs	
Maximum output power	6.000 W
Rated output power	5.500 W
Rated Current (AC)	23,9 A
Voltage regulator	AVR
Outlet (AC)	1 x 16 A, 1 x 32 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	420,0 cc
Fuel tank capacity	28,0 L
Fuel Consumption	3,0 L/h
Size (L x W x H)	730x570x577 mm
Weight	85,5 kg
Includes	
Wheel	x2
Recoil / Electric starting mode	✓ / ✓
Box	1 pc

HEAVY DUTY



- Powerful and heavy duty air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Electric start and battery
- LED work light
- Extra large fuel tank for maximum running time
- Wheels for easy transport
- Overload protection
- 2 year warranty, even for professional use

H195 x L80 x W120cm - 6pcs

GPG 6800E HD
PETROL GENERATOR

ARTICLE NUMBER	46098
Tech Specs	
Maximum output power	6.800 W
Rated output power	6.300 W
Rated Current (AC)	27,4 A
Voltage regulator	AVR
Outlet (AC)	1 x 16 A, 1 x 32 A
Outlet (DC)	1 x 8,3 A
Cylinder displacement	438,0 cc
Fuel tank capacity	28,0 L
Fuel Consumption	3,5 L/h
Size (L x W x H)	730x570x577 mm
Weight	88,0 kg
Includes	
Wheel	x2
Recoil / Electric starting mode	✓ / ✓
Box	1 pc

HEAVY DUTY

420cc
POWER

7,5 kVA

EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628

AVR
AUTOMATIC VOLTAGE REGULATOR

2 PRO
YEAR
WARRANTY

FUEL
MAX **28,0 Lt**

OVERLOAD PROTECTION

85,5
kg

LED



SP

NEW

GPG 7500TE HD
PETROL GENERATOR

REF.	47525
Tech Specs	
Rated voltage	400 V ~ 3 Ph 50 Hz
Max power (400V)	7,5 kVA
Max power (230V)	2,5 kVA
Rated power input (400V)	6,9 kVA
Rated power input (230V)	2,3 kVA
Rated output current (400V)	17,3 A
Rated output current (230V)	10,0 A
Voltage regulator	AVR
Outlet (AC)	1x 16 A, 1x 32 A
Outlet (DC)	1x 8,3 A
Cylinder displacement	420,0 cc
Fuel tank capacity	28,0 L
Running time	9 h
Starting mode	Recoil / Electric ignition
Size (L x W x H)	730x570x577 mm
Weight	85,5 kg
Box	1 pc

3ph

- Powerful and heavy duty air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Electric start and battery
- LED work light
- Extra large fuel tank for maximum running time
- Wheels for easy transport
- Overload protection
- Fast air filter access
- 2 year warranty, even for professional use

H 195 x L 80 x W 120cm - 6pcs

HEAVY DUTY

500cc
POWER

8,5 kVA

EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628

AVR
AUTOMATIC VOLTAGE REGULATOR

2 PRO
YEAR
WARRANTY

FUEL
MAX **28,0 Lt**

OVERLOAD PROTECTION

98
kg

LED



SP

GPG 8500E HD
PETROL GENERATOR

REF.	46099
Tech Specs	
Rated voltage	230 V 50 Hz
Max power	8,5 kVA
Rated power input	8,0 kVA
Rated output current	34,8 A
Voltage regulator	AVR
Outlet (AC)	2x 16 A, 1x 32 A
Outlet (DC)	1x 8,3 A
Cylinder displacement	500,0 cc
Fuel tank capacity	28,0 L
Running time	9 h
Starting mode	Recoil Electric ignition
Size (L x W x H)	730x570x577 mm
Weight	98,0 kg
Includes	
Rear wheel	x2
Work light (LED)	x1
Box	1 pc

- Powerful and heavy duty air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Electric start and battery
- LED work light
- Extra large fuel tank for maximum running time
- Wheels for easy transport
- Overload protection
- 2 year warranty, even for professional use

H 198 x L 80 x W 120cm - 6pcs

HEAVY DUTY

500cc
10,6 KVA
POWER

EURO 5
EMISSIONS COMPLIANT
EU REGULATION 2016/1628

AVR
AUTOMATIC VOLTAGE REGULATOR

2 PRO
YEAR
WARRANTY

FULL
POWER
3 PH > 1 PH

FUEL
MAX 28,0 Lt
OVERLOAD
PROTECTION

98
kg
LED



NEW

SP

GPG 10600TE HD
PETROL GENERATOR

REF.	47526
Tech Specs	
Rated voltage	400 V - 3 Ph 50 Hz
Max power (400V)	10,6 kVA
Max power (230V)	8,5 kVA
Rated power input (400V)	10,0 kVA
Rated power input (230V)	8,0 kVA
Rated output current (400V)	25,0 A
Rated output current (230V)	34,8 A
Voltage regulator	AVR
Outlet (AC)	2x 32 A
Outlet (DC)	1x 8,3 A
Cylinder displacement	500,0 cc
Fuel tank capacity	28,0 L
Running time	8 h
Starting mode	Recoil / Electric ignition
Size (L x W x H)	730x570x577 mm
Weight	98,0 kg
Box	1 pc

- Powerful and heavy duty air-cooled 4-stroke Euro5 engine with low vibrations and low emissions
- AVR voltage stabilization technology, for safe power supply of sensitive electric devices
- FULL POWER technology for 100% efficiency in either 230V or 400V
- 12V charging outlet
- Multiple alternating current outlets
- Low oil level safety
- Electric start and battery
- LED work light
- Extra large fuel tank for maximum running time
- Wheels for easy transport
- Overload protection
- Fast air filter access
- 2 year warranty, even for professional use

H198 x L80 x W120cm - 6pcs