

PRESSURE SENSOR

Stainless Steel pressure sensor with detachable cable.

TECHNICAL FEATURES

	MODEL		
	T-PS10	T-PS16	T-PS25
Measurement range	0-10 bar	0-16 bar	0-25 bar
Accuracy	+/-0,5 % F.S.		
Output signal	4... 20 mA		
Working temperature	- 20...+85 °C		
Pressure connection	G1/4		
Protection degree	IP 65		
Electrical connection	M12 waterproof outlet		
Material	SS AISI 304		
Cable lenght	1,5 mt		

MODEL	RANGE	CODE	PACKAGE
T-PS10	0-10 bar	RCIV00221	1 pcs.
T-PS16	0-16 bar	RCIV00203	1 pcs.
T-PS25	0-25 bar	RCIV00222	1 pcs.


Nota: Available on request:

- AISI 316
- Different pressure range
- Different power supply
- Temperature sensor

Cable connection



Dimensions mm



ULTRASONIC SENSOR

Measures level of liquids in the collection tanks.

TECHNICAL FEATURES

Measurement range	0,25 mt-4 mt
Accuracy	0.5 F.S.
Output signal	4-20 mA
Working temperature	-10 °C +50 °C
Max distance	4 mt
Blind zone	25cm
Protection degree	IP68
Reading corner	25°
Cable lenght	4 mt

MODEL	CODE	PACKAGE
T-US2.25	RCMP00101	1 pcs.
T-US4.25	RCMP00102	1 pcs.



Dimensions in mm

