



Pressure transmitter

MBS 3000 / MBS 3050

For general industrial purposes

Description

The compact pressure transmitter, type MBS 3000, is designed for use in industrial and hydraulic applications, and offers a reliable pressure measurement, even under harsh environmental conditions.

The compact heavy duty pressure transmitter MBS 3050 with integrated pulse-snubber is designed for use in hydraulic applications with severe medium influences like cavitation, liquid hammer or pressure peaks and offers a reliable pressure measurement, even under harsh environmental conditions.

The flexible pressure transmitter programme covers different output signals, absolute or gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar. A wide range of pressure and electrical connections are available.


Excellent vibration stability, robust construction, and a high degree of EMC/EMI protection equip the pressure transmitter to meet the most stringent industrial requirements.

Features & benefits

- Designed for use in severe industrial and hydraulic environments
- Resistant to cavitation, liquid hammer and pressure peaks (MBS 3050)
- Enclosure and wetted parts of acid-resistant stainless steel (AISI 316L)
- Pressure ranges in relative (gauge) or absolute from 0 up to 600 bar
- All standard output signals: 4 – 20 mA, 0 – 5 V, 1 – 5 V, 1 – 6 V, 0 – 10 V, 1 – 10 V, Ratiometric output signal: 10-90% of supply voltage
- A wide range of pressure and electrical connections
- Fully digitally compensated
- For use in ATEX zone 2 explosive atmospheres
- UL approved

Applications

Application and media conditions for MBS 3050



1 Pulse-snubber

Application for MBS 3050

Cavitation, liquid hammer and pressure peaks may occur in hydraulic systems with changes in flow velocity, e.g. fast closing of a valve or when a pump starts and stops.

The problem may occur on the inlet and outlet side of the application, even at rather low operating pressures.

Media condition for MBS 3050

Clogging of the nozzle may occur in liquids containing particles. Mounting the transmitter in an upright position minimizes the risk of clogging, because the flow in the nozzle is limited to the start-up period until the dead volume behind the nozzle orifice is filled. The media viscosity has only little effect on the response time. Even at a viscosities up to 100 cSt, the response time will not exceed 4 ms.



Ordering

Product code numbers

MBS 30..		[][] - [][] [][] - [][] [][] [][] - [][]																																	
		<table border="1"> <tr> <td colspan="2">Gasket / O-ring material</td> </tr> <tr> <td>0</td> <td>No gasket</td> </tr> <tr> <td>1</td> <td>Gasket, Viton -20°C - 125°C</td> </tr> <tr> <td>2</td> <td>Gasket, NBR -40°C - 100°C</td> </tr> <tr> <td>3</td> <td>O-ring, Viton -20°C - 125°C</td> </tr> <tr> <td>4</td> <td>O-ring, NBR -40°C - 100°C</td> </tr> </table>		Gasket / O-ring material		0	No gasket	1	Gasket, Viton -20°C - 125°C	2	Gasket, NBR -40°C - 100°C	3	O-ring, Viton -20°C - 125°C	4	O-ring, NBR -40°C - 100°C																				
Gasket / O-ring material																																			
0	No gasket																																		
1	Gasket, Viton -20°C - 125°C																																		
2	Gasket, NBR -40°C - 100°C																																		
3	O-ring, Viton -20°C - 125°C																																		
4	O-ring, NBR -40°C - 100°C																																		
		<table border="1"> <tr> <td colspan="2">Pressure connection</td> </tr> <tr> <td>AB04</td> <td>G ¼ A (EN 837) (MBS 3000 only)</td> </tr> <tr> <td>AB06</td> <td>G ⅜ A (EN 837) (MBS 3000 only)</td> </tr> <tr> <td>AB08</td> <td>G ½ A (EN 837)</td> </tr> <tr> <td>AC04</td> <td>¼ - 18 NPT</td> </tr> <tr> <td>AC08</td> <td>½ - 14 NPT (MBS 3000 only)</td> </tr> <tr> <td>GB04</td> <td>DIN 3852-E -G ¼,</td> </tr> <tr> <td>FA09</td> <td>DIN 3852-E-M14 x 1.5</td> </tr> <tr> <td>FA12</td> <td>DIN 3852/3, M18 x 1.5-6g</td> </tr> <tr> <td>FD10</td> <td>⅝- 18 UBF - 2A (SA EJ514)</td> </tr> </table>		Pressure connection		AB04	G ¼ A (EN 837) (MBS 3000 only)	AB06	G ⅜ A (EN 837) (MBS 3000 only)	AB08	G ½ A (EN 837)	AC04	¼ - 18 NPT	AC08	½ - 14 NPT (MBS 3000 only)	GB04	DIN 3852-E -G ¼,	FA09	DIN 3852-E-M14 x 1.5	FA12	DIN 3852/3, M18 x 1.5-6g	FD10	⅝- 18 UBF - 2A (SA EJ514)												
Pressure connection																																			
AB04	G ¼ A (EN 837) (MBS 3000 only)																																		
AB06	G ⅜ A (EN 837) (MBS 3000 only)																																		
AB08	G ½ A (EN 837)																																		
AC04	¼ - 18 NPT																																		
AC08	½ - 14 NPT (MBS 3000 only)																																		
GB04	DIN 3852-E -G ¼,																																		
FA09	DIN 3852-E-M14 x 1.5																																		
FA12	DIN 3852/3, M18 x 1.5-6g																																		
FD10	⅝- 18 UBF - 2A (SA EJ514)																																		
<table border="1"> <tr> <td>Standard</td> <td>00</td> </tr> <tr> <td>With pulse-snubber</td> <td>50</td> </tr> </table>		Standard	00	With pulse-snubber	50																														
Standard	00																																		
With pulse-snubber	50																																		
<table border="1"> <tr> <td colspan="2">Measuring range</td> </tr> <tr> <td>0 – 1 bar</td> <td>10</td> </tr> <tr> <td>0 – 1.6 bar</td> <td>12</td> </tr> <tr> <td>0 – 2.5 bar</td> <td>14</td> </tr> <tr> <td>0 – 4 bar</td> <td>16</td> </tr> <tr> <td>0 – 6 bar</td> <td>18</td> </tr> <tr> <td>0 – 10 bar</td> <td>20</td> </tr> <tr> <td>0 – 16 bar</td> <td>22</td> </tr> <tr> <td>0 – 25 bar</td> <td>24</td> </tr> <tr> <td>0 – 40 bar</td> <td>26</td> </tr> <tr> <td>0 – 60 bar</td> <td>28</td> </tr> <tr> <td>0 – 100 bar</td> <td>30</td> </tr> <tr> <td>0 – 160 bar</td> <td>32</td> </tr> <tr> <td>0 – 250 bar</td> <td>34</td> </tr> <tr> <td>0 – 400 bar</td> <td>36</td> </tr> <tr> <td>0 – 600 bar</td> <td>38</td> </tr> </table>		Measuring range		0 – 1 bar	10	0 – 1.6 bar	12	0 – 2.5 bar	14	0 – 4 bar	16	0 – 6 bar	18	0 – 10 bar	20	0 – 16 bar	22	0 – 25 bar	24	0 – 40 bar	26	0 – 60 bar	28	0 – 100 bar	30	0 – 160 bar	32	0 – 250 bar	34	0 – 400 bar	36	0 – 600 bar	38		
Measuring range																																			
0 – 1 bar	10																																		
0 – 1.6 bar	12																																		
0 – 2.5 bar	14																																		
0 – 4 bar	16																																		
0 – 6 bar	18																																		
0 – 10 bar	20																																		
0 – 16 bar	22																																		
0 – 25 bar	24																																		
0 – 40 bar	26																																		
0 – 60 bar	28																																		
0 – 100 bar	30																																		
0 – 160 bar	32																																		
0 – 250 bar	34																																		
0 – 400 bar	36																																		
0 – 600 bar	38																																		
		<table border="1"> <tr> <td colspan="2">Electrical connection</td> </tr> <tr> <td colspan="2">Figures refer to plug and standard PIN configuration - see "Electrical connection"</td> </tr> <tr> <td>A0</td> <td>4 pin male (EN 175301-803-A)</td> </tr> <tr> <td>A1</td> <td>Angular connector (EN 175301-803-A), Pg9</td> </tr> <tr> <td>A6</td> <td>Angular connector (EN 175301-803-A), Pg11</td> </tr> <tr> <td>A9</td> <td>Angular connector (EN 175301-803-A), Pg13.5</td> </tr> <tr> <td>C8</td> <td>Bayonet plug, ISO 15170-A1-3.2-Sn (Ratiometric output only)</td> </tr> <tr> <td>DG</td> <td>Cable screened ship, 3m</td> </tr> <tr> <td>E3</td> <td>*IEC 61076-2-101, M12x1, male excl. female plug</td> </tr> <tr> <td>F4</td> <td>Cable, screen, ship 2m</td> </tr> <tr> <td>H3</td> <td>Angular connector (EN 175301-803-A), M20.</td> </tr> </table>		Electrical connection		Figures refer to plug and standard PIN configuration - see "Electrical connection"		A0	4 pin male (EN 175301-803-A)	A1	Angular connector (EN 175301-803-A), Pg9	A6	Angular connector (EN 175301-803-A), Pg11	A9	Angular connector (EN 175301-803-A), Pg13.5	C8	Bayonet plug, ISO 15170-A1-3.2-Sn (Ratiometric output only)	DG	Cable screened ship, 3m	E3	*IEC 61076-2-101, M12x1, male excl. female plug	F4	Cable, screen, ship 2m	H3	Angular connector (EN 175301-803-A), M20.										
Electrical connection																																			
Figures refer to plug and standard PIN configuration - see "Electrical connection"																																			
A0	4 pin male (EN 175301-803-A)																																		
A1	Angular connector (EN 175301-803-A), Pg9																																		
A6	Angular connector (EN 175301-803-A), Pg11																																		
A9	Angular connector (EN 175301-803-A), Pg13.5																																		
C8	Bayonet plug, ISO 15170-A1-3.2-Sn (Ratiometric output only)																																		
DG	Cable screened ship, 3m																																		
E3	*IEC 61076-2-101, M12x1, male excl. female plug																																		
F4	Cable, screen, ship 2m																																		
H3	Angular connector (EN 175301-803-A), M20.																																		
<table border="1"> <tr> <td colspan="2">Pressure reference</td> </tr> <tr> <td>Gauge (relative)</td> <td>1</td> </tr> <tr> <td>Absolute</td> <td>2</td> </tr> <tr> <td>Sealed gauge</td> <td>3</td> </tr> </table>		Pressure reference		Gauge (relative)	1	Absolute	2	Sealed gauge	3	<table border="1"> <tr> <td colspan="2">Output signal</td> </tr> <tr> <td>1</td> <td>4 – 20 mA</td> </tr> <tr> <td>2</td> <td>0 – 5 V</td> </tr> <tr> <td>3</td> <td>1 – 5 V</td> </tr> <tr> <td>4</td> <td>1 – 6 V</td> </tr> <tr> <td>5</td> <td>0 – 10 V</td> </tr> <tr> <td>7</td> <td>1 – 10 V</td> </tr> <tr> <td>6</td> <td>Ratiometric, 10 – 90%</td> </tr> </table>		Output signal		1	4 – 20 mA	2	0 – 5 V	3	1 – 5 V	4	1 – 6 V	5	0 – 10 V	7	1 – 10 V	6	Ratiometric, 10 – 90%								
Pressure reference																																			
Gauge (relative)	1																																		
Absolute	2																																		
Sealed gauge	3																																		
Output signal																																			
1	4 – 20 mA																																		
2	0 – 5 V																																		
3	1 – 5 V																																		
4	1 – 6 V																																		
5	0 – 10 V																																		
7	1 – 10 V																																		
6	Ratiometric, 10 – 90%																																		
		<p>* Gauge versions only available as sealed gauge versions</p>																																	

Note: For a detailed overview of our existing code numbers, please visit the Danfoss Product Store at store.danfoss.com. You can use the filtering options to find the right sensor for your specific needs.

Product details

General data

Performance (EN 60770)

Accuracy (incl. non-linearity, hysteresis and repeatability)	$\leq \pm 0.5\% \text{ FS (typ.)}$
	$\leq \pm 1\% \text{ FS (max.)}$
Non-linearity BFSL (conformity)	$\leq \pm 0.2\% \text{ FS}$
Hysteresis and repeatability	$\leq \pm 0.1\% \text{ FS}$
Thermal zero point shift	$\leq \pm 0.1\% \text{ FS} / 10\text{K (typ.)}$
	$\leq \pm 0.2\% \text{ FS} / 10\text{K (max.)}$
Thermal sensitivity (span) shift	$\leq \pm 0.1\% \text{ FS} / 10\text{K (typ.)}$
	$\leq \pm 0.2\% \text{ FS} / 10\text{K (max.)}$
Response time: Liquids with viscosity < 100 cSt	< 4 ms
Response time: Air and gases (MBS 3050)	< 35 ms
Overload pressure (static)	6 × FS (max. 1500 bar)
Burst pressure	6 × FS (max. 2000 bar)
Power-up time	< 50 ms
Durability, P: 10 – 90% FS	> 10 × 10 ⁶ cycles
MTTFd - Calculation based on the SN 29500	> 100 years



Electrical specifications

Nom. output signal (short-circuit protected)	4 – 20 mA	0 – 5, 1 – 5, 1 – 6 V	0 – 10 V, 1 – 10 V	Ratiometric 10 – 90% of [U _B]
Supply voltage [U _B], polarity protected	9 – 32 V DC	9 – 32 V DC	15 – 32 V DC	4.5 – 5.5 V DC
Supply – current consumption	–	≤ 5 mA	≤ 8 mA	≤ 5 mA at 5 V DC
Supply voltage dependency	< 0.1% FS / 10 V	< 0.05% FS / 10 V		–
Ratiometricity	–	–		< 0.05% FS / 4.5 – 5.5 V
Output limitation	22.4 mA	0-5 V: 5.75 V 1-5 V: 5.6 V 1-6 V: 6.75 V	0-10V: 11.5 V	≈ supply voltage
Sink / Source	–	< 1 mA		
Load [R _L] (load connected to 0 V)	R _L ≤ (U _B - 9 V) / 0.02 A	R _L ≥ 10 kΩ	R _L ≥ 15 kΩ	R _L ≥ 10 kΩ at 5 V DC

Table: Environmental conditions

Sensor operating temperature	Normal		-40 – 85 °C
	ATEX Zone 2		-20 - 85°C
Media temperature range			-40 – 85 °C
Ambient temperature range (depending on electrical connection)			See Electrical connections
Compensated temperature range			0 – 80 °C
Transport/storage temperature range			-50 – 85 °C
EMC – Emission			EN 61000-6-3
EMC – Immunity			EN 61000-6-2
Insulation resistance			> 100 MΩ at 500 V DC
Vibration stability	Sinusoidal	15.9 mm-pp, 5 Hz – 25 Hz	IEC 60068-2-6
		20 g, 25 Hz – 2 kHz	
	Random	7.5 g _{rms} , 5 Hz – 1 kHz	IEC 60068-2-64
Shock resistance	Shock	500 g / 1 ms	IEC 60068-2-27
	Free fall	1 m	IEC 60068-2-32
Enclosure (depending on electrical connection)			See Electrical connections

Explosive atmospheres

Zone 2 applications ⁽¹⁾	  II 3G Ex ec IIA T3 Gc -20°C < Ta < +85°C	EN60079-0; EN60079-7
------------------------------------	---	----------------------








⁽¹⁾When used in ATEX Zone 2 areas at low temperatures the cable and plug must be protected against impact.

Mechanical characteristics

Materials	Wetted parts	EN 10088-1; 1.4404 (AISI 316 L)
	Enclosure	EN 10088-1; 1.4404 (AISI 316 L)
	Electrical connections	See Electrical connections
Net weight (depending on pressure connection and electrical connection)		0.2 – 0.3 kg

Connections

Electrical connections

Type code	A1 & A6	A3 & A0	E3	A8
	 EN 175301-803-A, Pg 9 & Pg 11	 2 m screened cable	 IEC 61076-2-101 M12 x 1; 4-pin	 AMP Superseal 1.5 series (male)
Ambient temperature	-40 – 85 °C	-30 – 85 °C	-25 – 90 °C	- 30 – 85 °C
Enclosure (IP protection fulfilled together with mating connector)	IP65	IP67	IP67	IP67
Atex Zone 2 enclosure	IP54			
Material	Glass filled polyamid, PA 6.6 ⁽¹⁾	Poliolyfin cable with PE shrinkage tubing	Nickel plated brass, CuZn/Ni	Glass filled polyamid, PA 6.6 ⁽²⁾
Electrical connection, 4 – 20 mA output (2 wire)	Pin1: + supply Pin 2: ÷ supply Pin 3: not used  Earth: Connected to MBS enclosure	Brown wire: + supply Black wire: ÷ supply Red wire: not used Orange: not used Screen: not connected to MBS enclosure	Pin1: + supply Pin 2: not used Pin 3: not used Pin 4: ÷ supply	Pin1: + supply Pin 2: ÷ supply Pin 3: not used
Electrical connection, 0 – 5 V, 1 – 5 V, 1 – 6 V, 0 – 10 V, 1 – 10 V output	Pin1: + supply Pin 2: ÷ supply/ common Pin 3: + output  Earth: Connected to MBS enclosure	Brown wire: + output Black wire: ÷ supply Red wire: + supply Orange: not used Screen: not connected to MBS enclosure	Pin1: + supply Pin 2: not used Pin 3: + output Pin 4: ÷ supply/ common	Pin1: + supply Pin 2: ÷ supply/ common Pin 3: + output
Electrical connection Ratiometric output, 10-90 % of supply voltage	Pin1: + supply Pin 2: ÷ supply Pin 3: output / common  Earth: Connected to MBS enclosure	Brown wire: output Black wire: ÷ supply Red wire: Common ⁽³⁾ Orange: not used Screen: not connected to MBS enclosure	Pin1: + supply Pin 2: not used Pin 3: output Pin 4: ÷ supply/ common	Pin1: + supply Pin 2: ÷ supply Pin 3: output/common




⁽¹⁾ Female plug: Glass filled polyester, PBT

⁽²⁾ Wire: PTFE (teflon) Protection sleeve: PBT mesh (polyester)

⁽³⁾ Common

NOTE: Please check store.danfoss.com to find the correct variant for your requirements.

Electrical connections (*continuous*)

Type code	C8	D9	G1
	 <p>ISO 15170-A1-3.2-Sn Bayonet</p>	 <p>AMP 173065, male Flying leads 125 mm</p>	 <p>AMP Econoseal J series (male)</p>
Ambient temperature	-40 – 85 °C	-40 – 85 °C	-30 – 85 °C
Enclosure (IP protection fulfilled together with mating connector)	IP67/IP69	IP67	IP67
Atex Zone 2 enclosure	IP54		
Material	Glass filled polyester PBT ⁽²⁾	Glass filled polyester PBT ⁽²⁾	Glass filled polyamide, PA 6.6 ⁽¹⁾
Electrical connection, 4 – 20 mA output (2 wire)	-	Pin 1: + supply Pin 2: - supply Pin 3: not used	Pin 1: + supply Pin 2: ÷ supply/ common Pin 3: not used
Electrical connection, 0 – 5 V, 1 – 5 V, 1 – 6 V, 0 – 10 V, 1 – 10 V output	-	Pin 1: + supply Pin 2: - supply Pin 3: + output	Pin 1: + supply Pin 2: ÷ supply/ common Pin 3: + output
Electrical connection Ratiometric output, 10-90 % of supply voltage	Pin 1: + supply Pin 2: ÷ supply/ common Pin 3: + output Pin 4: Not used	-	Pin 1: + supply Pin 2: ÷ supply/ common Pin 3: + output

⁽¹⁾ Female plug: Glass filled polyester, PBT

⁽²⁾ Wire: PTFE (teflon) Protection sleeve: PBT mesh (polyester)

⁽³⁾ Common

NOTE: Please check store.danfoss.com to find the correct variant for your requirements.

Certificates, declarations and approvals

The list contains all certificates, declarations, and approvals for this product type. Individual code number may have some or all of these approvals, and certain local approvals may not appear on the list.

When you click on the link you will be directed to the latest version of the 'Declaration of Conformity'. Products developed and sold before this date of issue conform to the directives/standards in force at the time of their sale.

Approval type	Title	Certification body	Approval topic
Pressure Safety Certificate	TSSA CRN.OF18477.5123467890YTN	TSSA - Technical Standards & Safety Authority	CRN
Electrical Safety Certificate	UL E510763	UL - Underwriters Laboratories inc.	
Electrical Safety Certificate	UL E494625	UL - Underwriters Laboratories inc.	
Manufacturer's Declaration	Danfoss MD 060R3160.00	Danfoss	China RoHS
Hygienic Certificate	NSF C863837	NSF International	Drinking Water
Electrical Safety Certificate	UL E311982	UL - Underwriters Laboratories inc.	
Export Control Declaration	Pressure & Temperature Sensors	Danfoss	
UA Declaration	Danfoss UA 2023-01-10 Regulators PL01 PL04	Danfoss	Pressure, PED
EU-UK Declaration	Danfoss EU-UK 064G9615.11	Danfoss	EMC, EU RoHS, ATEX, UK RoHS
Explosive Safety Certificate	UL E227388	UL - Underwriters Laboratories inc.	UL-CSA, Explosive
Hygienic Certificate	NSF C0252992	NSF International	Drinking Water
Electrical Safety Certificate	UL E31024	UL - Underwriters Laboratories inc.	
UA Declaration	Danfoss UA 2024-07-25 cooling sensors	Danfoss	LVD, EMC
Pressure Safety Certificate	LLC CDC EURO-TYSK UA.TR.089.1015.05-22	LLC CDC EURO TYSK - Ukraine	Pressure
EAC Declaration	EAC KZ 7100841.13.12.00005	EAC - Eurasian Customs Union	EMC

Contact details

Online support

Danfoss offers a wide range of support along with our products, including digital information, software, mobile apps and expert guidance. See the possibilities below.



The Danfoss Design center

Discover the Design Center, our advanced digital platform that streamlines product selection. With integrated tools and enhanced type pages, it's simpler than ever to access product information and documentation, and to select the right products. Check the availability of Danfoss products at partner locations and enjoy seamless transitions from selection to purchase with our basket-to-basket functionality. Whether you're buying from our distributors or directly from the Product Store, the Design Center simplifies your experience. Learn more at: designcenter.danfoss.com.



The Danfoss product store

The Danfoss Product Store is a one-stop shop available 24/7 for our customers, no matter where you are in the world or what area of industry you work in. Browse our catalog, check product details and documentation, view your prices and product availability, and quickly finalize your purchase. Start browsing at: store.danfoss.com.



Danfoss Partner Portal/Product Data tool

Designed to support you with easy access to product data extracts, essential resources, tools, and information. The Partner Portal provides a centralized hub for product documentation, training materials, marketing assets, and technical support, ensuring you have everything you need to succeed and grow your business with Danfoss. The Partner Portal is available 24/7 at: partner.danfoss.com and is ready to support your business.



Find technical documentation

Find technical documentation you need to get your project up running. Get direct access to our official collection of data sheets, certificates and declarations, manuals and guides, 3D models and drawings, case stories, brochures, and much more. Start searching now at: documentation.danfoss.com.



Danfoss Learning

Danfoss Learning is a free online learning platform. It features courses and materials specifically designed to help engineers, installers, service technicians, and wholesalers better understand the products, applications industry topics, and trends that will help you do your job better. Find your local Danfoss website here: learning.danfoss.com.



Get local information and support

Local Danfoss websites are the main sources for help and information about our company and products. Find product availability, get the latest regional news, or connect with a nearby expert - all in your own language. Find your local Danfoss website here: danfoss.com.

Danfoss A/S

Climate Solutions . danfoss.com . +45 7488 2222

Any information, including, but not limited to information on selection of product, its application or use, product design, weight, dimensions, capacity or any other technical data in product manuals, catalogues description, advertisements, etc. and whether made available in writing, orally, electronically, online or via download, shall be considered informative, and is only binding if and to the extent, explicit reference is made in a quotation or order confirmation. Danfoss cannot accept any responsibility for possible errors in catalogues, brochures, videos and other material. Danfoss reserves the right to alter its products without notice. This also applies to products ordered but not delivered provided that such alterations can be made without changes to form, fit or function of the products. All trademarks in this material are property of Danfoss A/S or Danfoss group companies. Danfoss and the Danfoss logo are trademarks of Danfoss A/S. All rights reserved.
